



NIXON SERIES

TECHNICAL FEATURES

Light Source Samsung LED

Luminaire Efficacy 80-90 lm/W

Chromaticity Tolerance (initial MacAdam) 3

Rated Median Useful Life* 50000h L70 at 25°C

Ballast 1x Lifud (5 Year Warranty)

Maintenance Category D - Enclosed IP2X

CUSTOM FEATURES

Optics Opal/Prismatic/Baffle

Light Distribution Direct and Direct-Indirect

Mounting Options Suspended/Surface Mount

Colour Rendering Index min. 80

Correlated Colour Temperature* 2700-6000k

Dimming 0-10v ,DALI

Linkable Power and Mechanically Linkable

Colours White, Black, Aluminium, Lawrence, Mission Bay, Rangitikei River, Custom

	Suspension Mount		Straight Connection
	Surface Mount		L Connect
	Ceiling Rose		T Connect
	End Cap		Cross Connect



DIRECT ILLUMINATION

Width/Height	Length	Power
62x82	573mm	15
62x82	853mm	22
62x82	1133mm	30
62x82	1413mm	38
62x82	1693mm	45
62x82	1793mm	52
62x82	2253mm	60
62x82	L Connect	15
62x82	T Connect	15
62x82	Cross Connect	15

DIRECT/INDIRECT ILLUMINATION

Width/Height	Length	Power
62x82	573mm	22.5
62x82	853mm	33
62x82	1133mm	45
62x82	1413mm	57
62x82	1693mm	67.5
62x82	1793mm	78
62x82	2253mm	90
62x82	L Connect	22.5
62x82	T Connect	22.5
62x82	Cross Connect	22.5

