

Low Wattage Adjustable Downlight



Model : FCA12

Physical

Trim finish White, Black

Mounting type Recessed

Tilt/Rotation angle

30°/None

30°/350° (FCF12-2/FCF12-3)

Electrical

Voltage

AC 220-240, 50/60 Hz

Control Non-dimmable,

Triac, Sunset dimmable,

1-10V, DALI

Optical

Beam angle 24°, 38°

CCT 2700, 3000, 4000, 5700, 6000K, 2000-3000K Sunset dim

CRI 90, 95 (Sunset dim), DWP

UGR < 19

Efficiency 66lm/W

Certification

Warranty 3 years

Category IP20, IP44 (FCE12)

AS/NZS 60598.2.2A

Product Specification

SKU	Wattage	Lumen Output (4000K)	Dimensions DxH/LxWxH mm	Cutout D/LxW mm	Technical Drawing
FCA12	12W	800lm	95 x 76	75	
FCB12	12W	800lm	98 x 86	85	
FCC12	12W	800lm	98 x 98 x 94	85 x 85	
FCD12	12W	800lm	95 x 95 x 86	75 x 75	
FCE12	12W	800lm	85 x 75	70	
FCF12-2	24W	2 x 800lm	200 x 110 x 74.5	100 x 190	
FCF12-3	36W	3 x 800lm	285 x 110 x 74.5	100 x 270	