

UDON 1023



Physical

Material Silicone with Silicone Opal diffuser

Mounting type Surface mounted

Power Feeds Multiple types depending on application

Electrical

Voltage and Current 24VDC

Control Non-dimmable, Triac, 1-10V, DALI

Max Run Per Power Feed
10m single power feed
20m dual power feed

Optical

Beam angle 270°

CCT 2700, 3000, 4000, 6000K, RGB, RGB Pixel

CRI 80, 90 (on request)


Certification

Warranty 2 years

Category IP65

Features

1 - Cuttable



2 - Seamless Joinable



3 - Power Feeds



Product Specification

SKU	Wattage (per m)	Lumen Output (per m) (2700K/3000K/4000K/6000k) (R/G/B)	Cuttable	Minimum Bend Radius	Dimensions WxH mm	Technical Drawing
FU1023	14.4 W	158/165/267/307 lm	100 mm	100 mm	10 x 23	
FU1023-RGB	14.4 W	24/52/13 lm	100 mm	100 mm	10 x 23	
FU1023-RGBP	10 W	24/52/13 lm	100 mm	100 mm	10 x 23	

Package

Udon 1023 is sold in a 10m pack with pre-attached Power Feed Bottom and End Cap. This pack also includes multiple accessories for most applications.

SKU	SKU per package
FU1023 / FU1023-RGB / FU1023-RGBP	1 x 10 m
FU1023-EC	4
FU1023-PFL	1
FU1023-PFR	1
FU1023-PFB	1
FU1023-MC	10

1 x 20 ml of Silicone Glue included in UDON package

Accessories

If additional accessories are required for a project please consult Novii.

SKU	Name	Technical Drawing
FU1023 / FU1023-RGB / FU1023-RGBP	UDON 1023	See Product Spec
FU1023-EC	End Caps	
FU1023-PFL	Power Feed Left	
FU1023-PFR	Power Feed Right	
FU1023-PFB	Power Feed Bottom	
FU1023-MC	Mounting Clip	
FU1023-MC-1M	Mounting Profile (1M Length)	