



LED Ringleuchte aus stranggepresstem Aluminium
Oberfläche eloxiert, weiß oder schwarz pulverbeschichtet
LED Konverter im Leuchtenprofil integriert
Inkl. flache PMMA-Abdeckung

LED ring luminaire, extruded aluminium
Anodised surface, white or black powder-coated
Built-in LED converter in profile
Incl. flat PMMA diffuser

Lampada in alluminio estruso a forma di anello
Superficie anodizzata o verniciata a polvere in bianco o nero
Converter LED integrato nel profilo
Incl. copertura piatta in PMMA

Lampe en forme d'anneau en aluminium extrudé
Finition anodisée ou laquée blanc ou noir
Convertiseur intégré dans le profil
Incl. couvercle plat en PMMA

W2 = LED 2700K
W3 = LED 3000K
W4 = LED 4000K

A+ - A

IP20

RIDE RING PD

220-240V AC/DC · CRI >90 · Binning SDCM 3 · DALI dimm.

SYS 38W / Ø 750mm	lm W2	lm W3	lm W4
675-20101102WXXd	3300	3590	3730

SYS 76W / Ø 1450mm	lm W2	lm W3	lm W4
675-20201102WXXd	6610	7180	7470

ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

W = LICHTFARBE/LIGHT COLOUR

W2 LED 2700K = 3
W3 LED 3000K = 9
W4 LED 4000K = 4

XX = FARBE/COLOUR

W white = 05
S black = 06
AE aluminium anodized = 08

