

# Beam Tracklight



Model : F25BT

## Physical

**Trim finish**  
White, Black, Custom colours

**Mounting type**  
Track mounted

**Rotation/Tilt angle**  
350°/90°

## Electrical

**Voltage**  
AC 220-240, 50/60 Hz

**Control**  
Switchable, Phase-cut

## Optical

**Beam angle**  
15°- 60°

**CCT**  
2700, 3000, 4000, 5000

**CRI**  
80, 90, 97

**UGR**  
< 19

**Efficiency**  
100lm/W


## Certification

**Warranty**  
5 years

**Category**  
IP20  
AS/NZS 60598.2.1

## Features

1 - Adjustable beam angle



2 - Cross ventilated design for increased lifetime



3 - Aluminium construction allowing RAL and custom colours



## Product Specification

SKU	Wattage	Lumen Output (4000K - 80CRI)	Dimensions A/B/C/D mm	Technical Drawing
F15BT	15W	500-1500lm	234/65/137/84.5	
F25BT	25W	750-2500lm	260/80/163/84.5	
F30BT	30W	1000-3000lm	265/100/173/84.5	

SKU

Accessories

FT-SM

Tracklight Surface Mount Kit

RoHS  

**fluxxLED**

## SKU Builder

Use our SKU Builder below to create custom codes from our range.

Series	Wattage	Type	Product Descriptor	Trim Finish	CRI	CCT	Beam Angle	Control
<b>F</b> FluxxLED	<b>15</b> 15W	<b>B</b> Beam	<b>T</b> Tracklight	<b>W</b> White	<b>8</b> 80 CRI	<b>27</b> 2700K	<b>A</b> 15°-60°	Switchable
	<b>25</b> 25W			<b>B</b> Black	<b>9</b> 90 CRI	<b>3</b> 3000K		<b>D</b> Phase-cut
	<b>30</b> 30W			<b>C</b> Custom colour	<b>97</b> 97 CRI	<b>4</b> 4000K		↑
						<b>5</b> 5000K		