

Cross Tracklight



Model : F25CT

Physical

Trim finish

White, Black, Custom colours

Mounting type

Track mounted

Rotation/Tilt angle

350°/90°

Electrical

Voltage

AC 220-240, 50/60 Hz

Control

Switchable, Phase-cut

Optical

Beam angle

15°, 24°, 36°

CCT

2700, 3000, 4000, 5000K

CRI

80, 90, 97

UGR

< 19

Efficiency

100lm/W

Certification

Warranty

5 years

Category

IP20

AS/NZS 60598.2.1

Features


1 - Cross ventilated design for increased lifetime



2 - Aluminium construction allowing RAL and custom colours



3 - Hot swappable reflector



Product Specification

SKU	Wattage	Lumen Output (4000K - 80CRI)	Dimensions A/B/C/D mm	Technical Drawing
F15CT	15W	1500lm	223/127/65/84.5	
F25CT	25W	2500lm	254/157/80/84.5	
F35CT	35W	3500lm	259/167/100/84.5	

SKU	Accessories
FT-SM	Tracklight Surface Mount Kit

SKU Builder

Use our SKU Builder below to create custom codes from our range

Series	Wattage	Type	Product Descriptor	Trim Finish	CRI	CCT	Beam Angle	Control
F FluxxLED	15 15W	C Cross	T Tracklight	W White	8 80 CRI	27 2700K	15 15°	Switchable
	25 25W			B Black	9 90 CRI	3 3000K	24 24°	D Phase-cut
	35 35W			C Custom colour	97 97 CRI	4 4000K	36 36°	↑
	↑			↑	↑	5 5000K	↑	
						↑		