

Flex Tile



Model: F3-FT23TW

Physical

Material Flexible PCB

Trim finish White

Mounting type

Surface mounted via screw & 3M Tape

Electrical

Voltage

24VDC

Control Non-dimmable,

1-10V, DALI

DALI DT8 (TW, RGB, RGBW, RGBTW)

Optical

Beam angle 120°

CCT 2000, 2200, 2500,

2700, 3000, 3500, 4000,

5000, 6000K

2700-6500K (Tunable white)

RGB, RGBW, RGBTW

CRI 80, 90

Efficiency 100lm/W

SDCM 3


Certification

Warranty 5 years


Category IP20

Lifetime L70B10 35000 Hrs
AS/NZS 60598.2.1

Features



Ultra slim 40mm lightboxes



Linkable power



Cutable sections

Product Specification

SKU	Wattage (per m)	Lumen Output (/m, @80CRI)		LED Colour	LED/pcs (per m)	Cutable (every mm)	Dimensions LxWxH mm	Technical Drawing
		(2700K/3000K/4000K/6000K)	(R/G/B-W)					
F3-FT12S	12W	1000/1150/1360/1300lm		White	140	240 x 25	500 x 240 x 8	
F3-FT23S	23W	1900/2000/2380/2300lm		White	288	60 x 40	480 x 240 x 8	
F3-FT23TW	23W	2000/2100/2440/2300lm		Tunable White	576	60 x 40	480 x 240 x 8	
F3-FT18RGB	18W	160/490/96lm		RGB	162	80 x 53.3	480 x 240 x 8	
F3-FT23RGBW	24W	180/510/105-700lm		RGB+ White	162	80 x 53.3	480 x 240 x 8	
F3-F26RGBTW	26W	160/490/96 - 646/680/800/752lm		RGB+ Tunable White	324	80 x 53.3	480 x 240 x 8	