

LED Strip 2835



Model: F3-LS283514

Physical

Material Flexible PCB
Trim finish White
Mounting type 3M Tape

Electrical

Voltage 24VDC
Control Non-dimmable, Triac, 1-10V, DALI
DALI DT8 (Tunable White only)

Optical

Beam angle 120°
CCT 2000, 2200, 2500, 2700, 3000, 3500, 4000, 5000, 6000K
2700-6500K (Tunable White)
CRI 80, 90
Efficiency 130-140lm/W
SDCM 3

Certification

Warranty 5 years
Category IP20/IP65
Lifetime (In Novii Profile) **L70B10** 35000 Hrs
AS/NZS 60598.2.1

Product Specification

SKU	Wattage (per m)	Lumen Output (/m, @80CRI) (2700/3000/4000/6000K)	LED Colour	LED/m	Cuttable (every mm)	Dimensions WxH mm	Length (/power feed)	Technical Drawing
F3-LS28359	9W	1146/1195/1260/1310lm	White	160	50	10 x 2	5m	
F3-LS283514	14.4W	1965/2050/2160/2245lm	White	160	50	10 x 2	5m	
F3-LS283517	17.28W	2220/2350/2430/2580lm	White	192	41.6	10 x 2	5m	
F3-LS283521	21.6W	2955/3035/3122/3235lm	White	240	33.3	10 x 2	5m	
F3-LS283518TW	18.54W	1085/2350/2400/1226lm	Tunable White	192	83.3	10 x 2	5m	