


## MICRO MD 8 35dg/840 HE



11




21

**SELV**



31

OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1516161	LED	340/58/60	332/50/60	0.70	1799	35°	17.0



CCT

4000 K

CRI

UGR

>80

<6

LED Service life

50000h L80B10 /SCDM3

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed linear downlighter ideal for accent illumination.

**OPTICS** Linear multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.




\*\* Add '-5' on ordering code for DALI control gear or

\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)

## MICRO MD 8 35dg/840 HO



11



220V  
240V



21

**SELV**




50Hz  
60Hz



31

OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1516166	LED	340/58/60	332/50/60	0.70	2799	35°	31.0



CCT

4000 K

CRI

UGR

>80

<6

LED Service life

50000h L80B10 /SCDM3

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed linear downlighter ideal for accent illumination.

**OPTICS** Linear multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.




\*\* Add '-5' on ordering code for DALI control gear or

\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)


## MICRO MD 8 55dg/840 HE



**SELV**



OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1516162	LED	340/58/60	332/50/60	0.70	1927	55°	17.0



CCT

4000 K

CRI

UGR

>80

<16

LED Service life

50000h L80B10 /SCDM3

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed linear downlighter ideal for accent illumination.

**OPTICS** Linear multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.




\*\* Add '-5' on ordering code for DALI control gear or

\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)


## MICRO MD 8 35dg/840 HO



**SELV**



OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1516167	LED	340/58/60	332/50/60	0.70	2997	55°	31.0



CCT

4000 K

CRI

UGR

>80

<19

LED Service life

50000h L80B10 /SCDM3

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed linear downlighter ideal for accent illumination.

**OPTICS** Linear multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.




\*\* Add '-5' on ordering code for DALI control gear or

\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)



## MICRO MD 8 75dg/840 HE



11




21

**SELV**



31

OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1516163	LED	340/58/60	332/50/60	0.70	2000	75°	17.0



CCT

4000 K

CRI

UGR

>80

<22

LED Service life

50000h L80B10 /SCDM3

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed linear downlighter ideal for accent illumination.

**OPTICS** Linear multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.




\*\* Add '-5' on ordering code for DALI control gear or

\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)

## MICRO MD 8 75dg/840 HO



11




21

**SELV**



31

OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1516168	LED	340/58/60	332/50/60	0.70	3111	75°	31.0



CCT

4000 K

CRI

UGR

>80

<25

LED Service life

50000h L80B10 /SCDM3

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed linear downlighter ideal for accent illumination.

**OPTICS** Linear multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.



\*\* Add '-5' on ordering code for DALI control gear or

\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)