




## MICRO QUADRO 35dg/840 HE



OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1514141	LED	100/100/60	92/92/60	0.40	900	35°	9.2



CCT	
4000 K	
CRI	UGR
>80	<6
LED Service life	
50000h L80B10 /SCDM3	

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed downlighter ideal for accent illumination.

**OPTICS** Multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.




\*\* Add '-5' on ordering code for DALI control gear or


\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)

## MICRO QUADRO 35dg/840 HO



OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1514146	LED	100/100/60	92/92/60	0.40	1399	35°	16.0



CCT	
4000 K	
CRI	UGR
>80	<6
LED Service life	
50000h L80B10 /SCDM3	

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed downlighter ideal for accent illumination.

**OPTICS** Multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.





\*\* Add '-5' on ordering code for DALI control gear or


\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)

## MICRO QUADRO 55dg/840 HE



OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1514142	LED	100/100/60	92/92/60	0.40	963	55°	9.2



CCT	
4000 K	
CRI	UGR
>80	<16
LED Service life	
50000h L80B10 /SCDM3	

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed downlighter ideal for accent illumination.

**OPTICS** Multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.




\*\* Add '-5' on ordering code for DALI control gear or

\*\* Add '-4' on ordering code for 1-10V control gear


\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)



## MICRO QUADRO 55dg/840 HO



OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1514147	LED	100/100/60	92/92/60	0.40	1499	55°	16.0



CCT

4000 K

CRI

UGR

>80

<19

LED Service life

50000h L80B10 /SCDM3

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed downlighter ideal for accent illumination.

**OPTICS** Multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.





\*\* Add '-5' on ordering code for DALI control gear or


\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)

## MICRO QUADRO 75dg/840 HE



OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1514143	LED	100/100/60	92/92/60	0.40	1000	75°	9.2



CCT	
4000 K	
CRI	UGR
>80	<22
LED Service life	
50000h L80B10 /SCDM3	

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed downlighter ideal for accent illumination.

**OPTICS** Multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.





\*\* Add '-5' on ordering code for DALI control gear or


\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)

## MICRO QUADRO 75dg/840 HO



OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
1514148	LED	100/100/60	92/92/60	0.40	1556	75°	16.0



CCT	
4000 K	
CRI	UGR
>80	<25
LED Service life	
50000h L80B10 /SCDM3	

**GENERAL** Minimal dimensions and supreme visual comfort together with high optical and energy efficiency make this recessed downlighter ideal for accent illumination.

**OPTICS** Multispot downlighter reflectors with complex surfaces geometry of micro facets allow precise shaping of light beam. Angles of direct light beam and light reflected from reflector are almost perfectly aligned, providing sharp cut off for full visual comfort.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into lighting management systems.

**HOUSING** Housing is made of aluminium with visible frame. Finish: epoxy polyester powder coating. Fine structured texture. Standard colours: white, gray, black, other colours available upon request.

**APPLICATION** Applicable to all types of suspended ceilings that can be cut through.

**ADDITIONAL** Dynamic White and other light colour temperatures available upon request.



\*\* Add '-5' on ordering code for DALI control gear or

\*\* Add '-4' on ordering code for 1-10V control gear

\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C)