

IP65 Round Bulkhead



Model: F3-12BR275

Physical

Material PC/Aluminium
Trim finish White, Black
Mounting type
Surface mounted

Electrical

Voltage
AC 220-240, 50/60 Hz
Control Non-dimmable,
Triac, 1-10V, DALI, Sensor,
Emergency

Optical

Beam angle 120°
CCT 2700, 3000, 4000,
5000, 5700K
CRI 80
UGR >19
Efficiency 95-110lm/W
SDCM 3

Certification

Warranty 5 years
Category IP65, IK10
Lifetime L70B10 >54000Hrs
AS/NZS 60598.2.1
AS/NZS 60598.2.22
Emergency on request

Features



Integrated
emergency option



IP65



IK10

Product Specification

| SKU | Wattage | Lumen Output (80CRI / 4000K) | Dimensions DxH mm | Technical Drawing |
|------------|---------|---------------------------------|----------------------|----------------------|
| F3-12BR275 | 12W | 1320lm | 275 x 59 | |
| F3-18BR275 | 18W | 1710lm | 275 x 59 | |
| F3-25BR275 | 25W | 2500lm | 275 x 59 | |
| F3-25BR350 | 25W | 2500lm | 350 x 59 | |
| F3-30BR350 | 30W | 2940lm | 350 x 59 | |