



GLARE CONTROL  
CIRCADIAN RHYTHM  
LIGHTING CONTROL  
FLICKER MANAGEMENT



## Balance Louvre

SKU	W	Lm @4000K/@80CRI	Cutout (mm)	Dimensions (mm)
G2-BL18SSP	18W	2520	280 x 580	
G2-BL25SP	25W	3500	580 x 580	
G2-BL25MP	25W	3500	280 x 1180	



\*Tunable White specifications available on request

SKU	Accessories
G2-BLRK	Recessed Kit for 1195 x 295 / 595 x 595 / 595 x 295
G2-BSM-SSP	Surface Mount Kit for 595 x 295
G2-BSM-SP	Surface Mount Kit for 595 x 595
G2-BSM-MP	Surface Mount Kit for 1195 x 295
G2-BSUS	Suspension Kit for 1195 x 295 / 595 x 595 / 595 x 295

### Physical

**Housing** PC/SPCC

**Trim Finish** White

**Mounting Type** Recessed, Surface Mounted, Suspended

### Electrical

**Voltage**

AC 220-240v 50/60Hz

**Control**

Non-dimmable, Triac, 1-10V, DALI, TW (DALI DT8)

### Optical

**Beam Angle**



100°

**CCT** 2700, 3000, 4000, 5700K  
2700-6500K (Tunable White)\*

**CRI** 80, 90

**UGR** < 16

**Efficiency** 140lm/W

### Certification

**Warranty** 5 years

**Category**

AS/NZS 60598.2.2A

TM21 report on request



IP40