



GLARE CONTROL
CIRCADIAN RHYTHM
LIGHTING CONTROL
FLICKER MANAGEMENT



Balance Micro

SKU	W	Lm @4000K/@80CRI	Cutout (mm)	Dimensions (mm)
G2-BM35SP	35W	4035	580 x 580	
G2-BM35MP	35W	4035	280 x 1180	



* Tunable White specifications available on request

SKU	Accessories
G2-BRK	Recessed Kit for 1195 x 295 / 595 x 595
G2-BSM-SP	Surface Mount Kit for 595 x 595
G2-BSM-MP	Surface Mount Kit for 1195 x 295
G2-BSUS	Suspension Kit for Balance 1195 x 295 / 595 x 595

Physical

Housing Aluminium

Trim Finish White

Mounting Type Recessed, Surface Mounted, Suspended

Electrical

Voltage

AC 220-240v 50/60Hz

Control

Non-dimmable, Triac, 1-10V, DALI, TW (DALI DT8)

Optical

Beam Angle



90°

CCT 2700, 3000, 4000, 5700K
2700-6500K (Tunable White)*

CRI 80, 90

UGR < 19

Efficiency 115lm/W

Certification

Warranty 5 years

Category

AS/NZS 60598.2.2A
TM21 report on request



grace