



GLARE CONTROL  
CIRCADIAN RHYTHM  
LIGHTING CONTROL  
FLICKER MANAGEMENT



# Balance Micro

SKU	W	Lm @4000K/@80CRI	Cutout (mm)	Dimensions (mm)
G2-BM35SP	35W	4035	580 x 580	
G2-BM35MP	35W	4035	280 x 1180	

CE RoHS



Tunable White  
Technology

\* Tunable White specifications  
available on request

SKU	Accessories
G2-BRK	Recessed Kit for 1195 x 295 / 595 x 595
G2-BSM-SP	Surface Mount Kit for 595 x 595
G2-BSM-MP	Surface Mount Kit for 1195 x 295
G2-BSUS	Suspension Kit for Balance 1195 x 295 / 595 x 595

### Physical

**Housing** Aluminium

**Trim Finish** White

**Mounting Type** Recessed,  
Surface Mounted, Suspended

### Electrical

**Voltage**

AC 220-240v 50/60Hz

**Control**

Non-dimmable, Triac,  
1-10V, DALI, TW (DALI DT8)

### Optical

**Beam Angle**



90°

**CCT** 2700, 3000, 4000, 5700K  
2700-6500K (Tunable White)\*

**CRI** 80, 90

**UGR** < 19

**Efficiency** 115lm/W

### Certification

**Warranty** 5 years

**Category**

AS/NZS 60598.2.2A  
TM21 report on request



IP40