



Compose Diffuse

SKU	W	Lm @4000K/@80CRI	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-C1D10	10	700	Fixed	Ø 82-88	
G2-C2D13	13	900	Fixed	Ø 90-95	
G2-C3D10	10	800	Fixed	Ø 125-135	
G2-C3D18	18	1600	Fixed	Ø 125-135	
G2-C3D25	25	2000	Fixed	Ø 125-135	
G2-C4D18	18	1700	Fixed	Ø 150-165	
G2-C4D25	25	2200	Fixed	Ø 150-165	
G2-C4D35	35	2870	Fixed	Ø 150-165	
G2-C5D18	18	1760	Fixed	Ø 200-210	
G2-C5D25	25	2350	Fixed	Ø 200-210	
G2-C5D35	35	3650	Fixed	Ø 200-210	
G2-C5D45	45	4360	Fixed	Ø 200-210	

Physical

Housing PC/Aluminium
Reflector Finish Black, White, Specular Silver, Matte Silver
Trim Finish White, Black
Mounting Type Recessed

Electrical

Voltage
 AC 220-240v 50/60Hz
Control
 Non-dimmable, Triac, 1-10V, DALI, TW (DALI DT8)

Optical

Beam Angle



CCT 2700K, 3 CCT Switch (3000, 4000, 5700K), 2700-6500K (Tunable White)*

CRI 80, 90

SDCM 3

UGR < 19

Efficiency 70-106lm/W

Certification

Warranty 5 years

Category
 AS/NZS 60598.2.2A
 TM21 report on request



Tunable White
Technology

* Tunable White specifications
available on request