



GLARE CONTROL  
LIGHTING CONTROL  
FLICKER MANAGEMENT



## Compose Lens

SKU	W	Lm @4000K	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-C1L10	10	900	Fixed	Ø 82-88	
G2-C2L13	13	1200	Fixed	Ø 90-95	
G2-C3L10	10	1150	Fixed	Ø 125-135	
G2-C3L18	18	2100	Fixed	Ø 125-135	
G2-C3L25	25	2700	Fixed	Ø 125-135	
G2-C4L18	18	2100	Fixed	Ø 150-165	
G2-C4L25	25	2700	Fixed	Ø 150-165	
G2-C4L35	35	3500	Fixed	Ø 150-165	
G2-C5L18	18	2100	Fixed	Ø 200-210	
G2-C5L25	25	2700	Fixed	Ø 200-210	
G2-C5L35	35	3700	Fixed	Ø 200-210	
G2-C5L45	45	4200	Fixed	Ø 200-210	

### Physical

**Housing** PC/Aluminium

**Reflector Finish** Black, White, Faceted Silver, Matte Silver

**Trim Finish** White, Black

**Mounting Type** Recessed

### Electrical

**Voltage**


AC 220-240v 50/60Hz

**Control**

Non-dimmable, Triac, 1-10V, DALI

### Optical

**Beam Angle**



**CCT** 2700, 3000, 4000, 5000K

**CRI** 80, 90

**UGR** < 19

**Efficiency** 90-115lm/W

### Certification

**Warranty** 5 years

**Category**

AS/NZS 60598.2.2A

TM21 report on request

