



GLARE CONTROL
LIGHTING CONTROL
FLICKER MANAGEMENT



Compose Lens

SKU	W	Lm @4000K	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-C1L10	10	1090	Fixed	Ø 82-88	
G2-C2L13	13	1305	Fixed	Ø 90-95	
G2-C3L10	10	1130	Fixed	Ø 125-135	
G2-C3L18	18	1975	Fixed	Ø 125-135	
G2-C3L25	25	2825	Fixed	Ø 125-135	
G2-C4L18	18	1980	Fixed	Ø 150-165	
G2-C4L25	25	2580	Fixed	Ø 150-165	
G2-C5L18	18	1835	Fixed	Ø 200-210	
G2-C5L25	25	2550	Fixed	Ø 200-210	
G2-C5L35	35	3190	Fixed	Ø 200-210	



* Only < 13W

* Asymmetric wall washing beam angle only available for C2/C3 sizes

Physical

Housing PC/Aluminium

Reflector Finish Black, White, Silver, Matte Silver

Trim Finish White, Black

Mounting Type Recessed

Electrical

Voltage


AC 220-240v 50/60Hz

Control

Non-dimmable, Triac, 1-10V, DALI

Optical

Beam Angle



CCT 2700, 3000, 4000, 5000K

CRI 90, 97CRI

SDCM 3

UGR < 19

Efficiency >100lm/W @4000K

Certification

Warranty 5 years

Lifetime L90 54,000Hrs

Category

AS/NZS 60598.2.2A

