



Flow Round

SKU	W	Lm @4000K/@80CRI	Light Distribution	Dimensions (mm)
G2-FR40D	40W	4000	Direct	
G2-FR40I	40W	4000	Direct/Indirect	
G2-FR60D	60W	6000	Direct	
G2-FR60I	60W	6000	Direct/Indirect	
G2-FR80D	80W	8000	Direct	
G2-FR80I	80W	8000	Direct/Indirect	
G2-FR100D	100W	10000	Direct	
G2-FR100I	100W	10000	Direct/Indirect	

Physical

Housing Aluminium

Trim Finish White, Black, Custom colours on request

Mounting Type

Surface Mounted, Suspended

Electrical

Voltage

AC 220-240v 50/60Hz

Control

Non-dimmable, DALI, TW (DALI DT8)

Optical

Beam angle



90°

CCT 2700, 3000, 4000, 5000K 2700-6500K (Tunable White)*

CRI 80, 90

UGR < 19

Efficiency 100lm/W

Certification

Warranty 5 years

Category

AS/NZS 60598.2.1

TM21 report on request



IP40



Tunable White Technology

* Tunable White specifications available on request

SKU	Accessories
G2-FRSUS	Suspension Kit
G2-FRWHS	Harness Suspension Kit
G2-FRPRS	Rod Suspension