



# Thrive

## Adjustable SM

SKU	W	Lm @4000K/@90CRI/55°	Tilt (T) Rotation (R) °	Dimensions (mm)
G2-TSM12RA	12W	850	25°T 350°R	164 110
G2-TSM12SA	12W	850	25°T 350°R	164 110
G2-TSM24RA	24W	2496	25°T 350°R	193 135
G2-TSM24SA	24W	2393	25°T 350°R	193 135
G2-TSM33RA	33W	3174	25°T 350°R	220 160
G2-TSM33SA	33W	3091	25°T 350°R	220 160

### Physical

**Housing** Aluminium  
**Reflector Finish** Black, White  
**Trim Finish** White, Black  
**Mounting Type** Surface Mounted

### Electrical

**Voltage** AC 220-240v 50/60Hz  
**Control** Non-dimmable  
 Triac, 1-10V, DALI (24-33W Only)

### Optical

**Beam Angle**  
  
 15° 24° 38° 55°  
**CCT** 2700, 3000, 4000, 5000K  
**CRI** 90, Thrive\*  
**UGR** < 19  
**Efficiency** 70-104lm/W

### Certification

**Warranty** 5 years  
**Category** AS/NZS 60598.2.1  
 TM21 report on request



\* Thrive LED specifications available on request