



- GLARE CONTROL
- NATURAL LIGHT
- LIGHTING CONTROL
- FLICKER MANAGEMENT

## Thrive

### Adjustable SM

SKU	W	Lm @4000K/@90CRI/55°	Tilt (T) Rotation (R) °	Dimensions (mm)
G2-TSM12RA	12W	850	25°T 350°R	
G2-TSM12SA	12W	850	25°T 350°R	
G2-TSM24RA	24W	2496	25°T 350°R	
G2-TSM24SA	24W	2393	25°T 350°R	
G2-TSM33RA	33W	3174	25°T 350°R	
G2-TSM33SA	33W	3091	25°T 350°R	


#### Physical

- Housing** Aluminium
- Reflector Finish** Black, White
- Trim Finish** White, Black
- Mounting Type** Surface Mounted

#### Electrical

- Voltage** AC 220-240v 50/60Hz
- Control** Non-dimmable  
Triac, 1-10V, DALI (24-33W Only)

#### Optical

- Beam Angle**

- CCT** 2700, 3000, 4000, 5000K
- CRI** 90, Thrive\*
- UGR** < 19
- Efficiency** 70-104lm/W

#### Certification

- Warranty** 5 years
- Category** AS/NZS 60598.2.1  
TM21 report on request



\* Thrive LED specifications available on request