

# Thrive Optical

SKU	W	Lm @4000K/@90CRI/38°	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-TO12P	12	824	Fixed	Ø 75	
G2-TO12GR	12	972	23°T	Ø 75	
G2-TO12SP	12	830	Fixed	Ø 75	
G2-TO12SW	12	869	23°T	Ø 75	
G2-TO12RAW	12	977	23°T	Ø 90	
G2-TO12RA	12	1089	15°T	Ø 70	
G2-TO12SA	12	1089	15°T	Ø 70	
G2-TO12R (IP54)	12	920	Fixed	Ø 75	

### Physical

**Housing** Aluminium

**Trim Finish** White, Black

**Mounting Type** Recessed

### Electrical

**Voltage**


AC 220-240v 50/60Hz

**Control**

Non-dimmable, Triac,  
1-10V, DALI

### Optical

**Beam Angle**



**CCT** 2700, 3000, 4000, 5000K

**4545CRI** 90, Thrive\*

**UGR** < 19

**Efficiency** 70-91lm/W

### Certification

**Warranty** 5 years

**Category**

AS/NZS 60598.2.2A

TM21 report on request



Bridgelux Thrive  
LED technology

\* Thrive LED specifications  
available on request