



GLARE CONTROL

LIGHTING CONTROL

FLICKER MANAGEMENT



Balance Prismatic

SKU	W	Lm @4000K/@80CRI	Cutout (mm)	Dimensions (mm)
G2-BP16SSP	16W	1760	280 x 580	
G2-BP30SP	30W	3300	580 x 580	
G2-BP30MP	30W	3300	280 x 1180	
G2-BP50LP	50W	5500	580 x 1180	

Physical

Housing Aluminium

Trim Finish White

Mounting Type Recessed,
Surface Mounted, Suspended

Electrical

Voltage
AC 220-240v 50/60Hz

Control
Non-dimmable, Triac,
1-10V, DALI

Optical

Beam Angle



90°

CCT 2700, 3000, 4000, 5000K

CRI 80, 90

UGR < 19

Efficiency 110lm/W

Certification

Warranty 5 years

Category
AS/NZS 60598.2.2A
TM21 report on request



IP40



SKU	Accessories
G2-BSM-SSP	Surface Mount Kit for 295 x 595
G2-BSM-SP	Surface Mount Kit for 595 x 595
G2-BSM-MP	Surface Mount Kit for 1195 x 295
G2-BSM-LP	Surface Mount Kit for 1195 x 595
G2-BRK	Recessed Kit for 1195 x 295 / 595 x 595 / 295 x 595
G2-BRK-LP	Recessed Kit for 1195 x 595
G2-BSUS	Suspension Kit for 1195 x 295 / 595 x 595 / 295 x 595
G2-BSUS-LP	Suspension Kit for 1195 x 595