



GLARE CONTROL

CIRCADIAN RHYTHM

LIGHTING CONTROL

FLICKER MANAGEMENT

# Flow Round

| SKU       | W    | Lm @4000K/@80CRI | Light Distribution | Dimensions (mm) |
|-----------|------|------------------|--------------------|-----------------|
| G2-FR40D  | 40W  | 4000             | Direct             |                 |
| G2-FR40I  | 40W  | 4000             | Direct/Indirect    |                 |
| G2-FR60D  | 60W  | 6000             | Direct             |                 |
| G2-FR60I  | 60W  | 6000             | Direct/Indirect    |                 |
| G2-FR80D  | 80W  | 8000             | Direct             |                 |
| G2-FR80I  | 80W  | 8000             | Direct/Indirect    |                 |
| G2-FR100D | 100W | 10000            | Direct             |                 |
| G2-FR100I | 100W | 10000            | Direct/Indirect    |                 |

### Physical

**Housing** Aluminium  
**Trim Finish** White, Black, Custom colours on request  
**Mounting Type** Surface Mounted, Suspended

### Electrical

**Voltage** AC 220-240v 50/60Hz

### Control

Non-dimmable, DALI, TW (DALI DT8)

### Optical

#### Beam angle



**CCT** 2700, 3000, 4000, 5700K 2700-6500K (Tunable White)\*

**CRI** 80, 90

**UGR** < 19

**Efficiency** 100lm/W

### Certification

**Warranty** 5 years

### Category

AS/NZS 60598.2.1  
 TM21 report on request



Tunable White Technology

\* Tunable White specifications available on request

| SKU      | Accessories                         |
|----------|-------------------------------------|
| G2-FRSUS | Suspension Kit                      |
| G2-FRWHS | Harness Suspension Kit              |
| G2-FRPRS | Rod Suspension (only for 40W & 60W) |