

# Thrive Gyro

SKU	W	Lm @4000K/@90CRI/55°	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-TP12RA	12W	905	25°T 350°R	Ø 80	
G2-TP12SA	12W	912	25°T 350°R	Ø 80	
G2-T2P12RA	2 x 12W	2 x 905	25°T 350°R	80 x 165	
G2-TP24RA	24W	2414	20°T 355°R	Ø 95	
G2-TP24SA	24W	2482	20°T 355°R	Ø 95	
G2-T2P24RA	2 x 24W	2 x 2414	20°T 355°R	95 x 205	
G2-TP33RA	33W	3285	20°T 355°R	Ø 115	
G2-TP33SA	33W	3178	20°T 355°R	Ø 115	
G2-T2P33RA	2 x 33W	2 x 3285	20°T 355°R	115 x 245	

### Physical

**Housing** Aluminium

**Trim Finish** White, Black

**Mounting Type** Recessed

### Electrical

**Voltage**


AC 220-240v 50/60Hz

**Control**

Non-dimmable, Triac,  
1-10V, DALI

### Optical

**Beam Angle**



**CCT** 2700, 3000, 4000, 5000K

**CRI** 90, Thrive\*

**UGR** < 19

**Efficiency** 75-100lm/W

### Certification

**Warranty** 5 years

**Category**

AS/NZS 60598.2.2A

TM21 report on request



\* Thrive LED specifications available on request