



- GLARE CONTROL
- NATURAL LIGHT
- LIGHTING CONTROL
- FLICKER MANAGEMENT

Thrive Reflector

SKU	W	Lm @4000K/@90CRI/55°	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-TR12TA	12W	840	30°T 355°R	Ø 76	
G2-TR12T	12W	840	Fixed	Ø 76	
G2-TR12RA	12W	840	30°T 355°R	Ø 75	
G2-TR12R	12W	840	Fixed	Ø 75	
G2-TR12SA	12W	840	30°T	Ø 75	
G2-TR12RA2	12W	1020	30°T 355°R	Ø 95	
G2-TR12RA3	12W	1020	30°T 355°R	Ø 95	
G2-TR24RA	24W	2198	30°T 355°R	Ø 100	


Physical

- Housing** Aluminium
- Reflector Finish** Black, Specular Silver, Matte Silver
- Trim Finish** White, Black
- Mounting Type** Trimless, Recessed

Electrical

- Voltage** AC 220-240v 50/60Hz
- Control** Non-dimmable, Triac, 1-10V, DALI

Optical

- Beam Angle**
- 
- 15° 24° 38° 55°

- CCT** 2700, 3000, 4000, 5000K
- CRI** 90, Thrive*
- UGR** < 19
- Efficiency** 70-100lm/W

Certification

- Warranty** 5 years
- Category** AS/NZS 60598.2.2A
TM21 report on request



SKU	W	Lm @4000K/@90CRI/55°	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions
G2-TR24R	24W	2161	Fixed	Ø 100	
G2-TR24SA	24W	2156	25°T	Ø 100	
G2-TR-24RA2	24W	2472	30°T 355°R	Ø 110	
G2-TR-24RA3	24W	2332	30°T 355°R	Ø 110	
G2-TR-33RA	33W	2784	25°T 355°R	Ø 125	
G2-TR33R	33W	2848	Fixed	Ø 125	
G2-TR-33SA	33W	2795	25°T	Ø 125	
G2-TR-33RA2	24W	3292	30°T 355°R	Ø 130	
G2-TR-33RA3	33W	2996	30°T 355°R	Ø 130	



Bridgelux Thrive
LED technology

* Thrive LED
specifications

* Only 12W * Above 12W