

# Commercial Adjustable Downlight



Model : F30CRD

## Physical

**Trim finish** White, Black  
**Mounting type** Recessed  
**Tilt angle** 30°

## Electrical

**Voltage** AC 220-240, 50/60 Hz  
**Control** Non-dimmable, Triac, 1-10V, DALI

## Optical

**Beam angle** 15°, 24°, 40°, 60°  
**CCT** 2700, 3000, 3500, 4000, 5000K  
**CRI** 80, 90, DWP  
**UGR** < 19  
**Efficiency** 100lm/W  
**SCDM** 3


## Certification

**Warranty** 5 years  
**Category** IP20  
**Lifetime L70B10** >40000 Hrs  
 AS/NZS 60598.2.2A


## Features



Adjustable



Mutiple Beam Angles



DWP LED Technology

## Product Specification

SKU	Wattage	Lumen Output (80CRI / 4000K)	Dimensions DxH/LxWxH mm	Cutout D mm (LxW mm)	Technical Drawing
F30CRD	35W	3500lm	138 x 110	125	
F30CSD	35W	3500lm	175 x 175 x 167	160 x 160	
F30TSD	2 x 35W	7000lm	330 x 175 x 130	315 x 160	

Lighting Calculation Note : F30TSD can be created by placing 2 x F30CSD next to each other