



Physical

Housing Aluminium
Profile Colour White, Black, Custom colours on request
Mounting Type Recessed, Surface Mounted, Suspended

Electrical

Voltage AC 220-240v 50/60Hz
Control Non-dimmable, 0-10V, DALI

Optical

Beam Angle



80° 115° (Up)

CCT 2700, 3000, 4000, 6500K

CRI 80, 90

UGR < 19

Efficiency Up to 133lm/W

SDCM 3

Certification

Warranty 5 years

Category

AS/NZS 60598.2.1

LM-80 report on request


Lifetime L70 >54000 h




Lower outputs available upon request. Standard profile lengths are listed, consult Novii for custom lengths and connector angles. All lengths are stated with internal drivers, smaller lengths are possible with drivers housed in adjoining N-Series lengths. Tunable White versions of 841mm, 561mm and 281mm lengths need drivers housed in adjoining N-Series lengths. Tunable White L/T/X are larger due to driver length, consult Novii for lengths. Indirect DALI models are available in single or dual DALI control. All L/T/X connectors have internal drivers. 5% Tolerance on stated lumen output and wattage.

Direct

Surface Mounted, Suspended



Recessed



Length (mm)	W	Lm @4000K/@80CRI
281	7.5W	998
561	15W	1996
841	22W	2928
1121	30W	3992
1401	38W	5208
1681	45W	5988
1961	52W	6920
2241	60W	7984



LM-80

Accessories


SKU	Accessories
T2-NECAO	Surface mounted/Suspended profile end cap (single)
T2-NECRAO	Recessed profile end cap (single)
T2-SUS	Suspension kit (4m cable, pair)
T2-NSCD	Straight connector direct (Single)
T2-NSCI	Straight connector indirect (Single)

SKU Builder

Series	Length	Optic	Profile Type	Profile Colour	Optic Colour	CRI	CCT	Control	
T2-N	281	D (Daisy)	D (Direct)	B (Black)	B (Black)	8 (80)	27 (2700K)	N (Non-dim)	
	561		I (Direct/Indirect)	W (White)		9 (90)	3 (3000K)	D10 (0-10V)	
	841		DR (Recessed)	C (Custom Col)			4 (4000K)	DA (DALI)	
	1121								TDA (Tridonic DALI)
	1401								
1681									
	1961								
	2241								

Indirect

Suspended



Length (mm)	W	Lm @4000K/@80CRI
281	4W	539
561	8W	1077
841	13W	1750
1121	16W	2154
1401	19W	2558
1681	24W	3231
1961	28W	3770
2241	32W	4308

For combined Direct/Indirect data download IES file from website

SKU	Accessories
T2-NWC	Wall clip (Pair)
T2-NCR	Ceiling rose (Single)
T2-NRS	Rod suspension (1m, pair)
T2-NSM	Surface mounted kit (Pair)
T2-NBP	Blanking plate (1m)