



## N-SERIES HONEYCOMB

### Physical

**Housing** Aluminium

**Profile Colour** White, Black, Custom colours on request

### Mounting Type

Recessed, Surface Mounted, Suspended

### Electrical

#### Voltage


AC 220-240v 50/60Hz

#### Control

Non-dimmable, 0-10V, DALI, DALI DT8 (Tunable white)

### Optical

#### Beam Angle



85° (White) 65° (Black) 115° (Up)

**CCT** 2700, 3000,

4000, 6500K

2700-6500K (Tunable White)

**CRI** 80, 90

#### UGR

White Honeycomb > 19

Black Honeycomb < 19

**Efficiency** Up to 113lm/W

**SDCM** 3

### Certification

**Warranty** 5 years

### Category

AS/NZS 60598.2.1

LM-80 report on request

**Lifetime** L90 >54000 h



Lower outputs available upon request. Standard profile lengths are listed, consult Novii for custom lengths and connector angles.

All lengths are stated with internal drivers, smaller lengths are possible with drivers housed in adjoining N-Series lengths.

Tunable White versions of 841mm, 561mm and 281mm lengths need drivers housed in adjoining N-Series lengths.

Tunable White L/T/X are larger due to driver length, consult Novii for lengths.


Indirect DALI models are available in single or dual DALI control.

All L/T/X connectors have internal drivers.


5% Tolerance on stated lumen output and wattage.

### Direct

Surface Mounted, Suspended



Recessed



Length (mm)	W	Lm @4000K/@80CRI	
		White	Black
281	7W	716	269
561	14W	1432	538
841	20W	2046	769
1121	27W	2763	1038
1401	35W	3581	1346
1681	41W	4195	1576
1961	47W	4809	1807
2241	54W	5525	2076
L (548x548)	26W	2660	1000




LM-80

### Accessories

SKU	Accessories
T2-NECAO	Surface mounted/Suspended profile end cap (single)
T2-NECRAO	Recessed profile end cap (single)
T2-SUS	Suspension kit (4m cable, pair)
T2-NSCD	Straight connector direct (Single)
T2-NSCI	Straight connector indirect (Single)

### Indirect

Suspended



Length (mm)	W	Lm
		@4000K/@80CRI
281	4W	539
561	8W	1077
841	13W	1750
1121	16W	2154
1401	19W	2558
1681	24W	3231
1961	28W	3770
2241	32W	4308
L (548x548)	16W	2154

For combined Direct/Indirect data download IES file from website

SKU	Accessories
T2-NWC	Wall clip (Pair)
T2-NCR	Ceiling rose (Single)
T2-NRS	Rod suspension (1m, pair)
T2-NSM	Surface mounted kit (Pair)
T2-NBP	Blanking plate (1m)

### SKU Builder

Series	Length	Optic	Profile Type	Profile Colour	Optic Colour	CRI	CCT	Control
T2-N	281	H (Honeycomb)	D (Direct)	B (Black)	B (Black)	8 (80)	27 (2700K)	N (Non-dim)
	561		I (Direct/Indirect)	W (White)	W (White)	9 (90)	3 (3000K)	D10 (0-10V)
	841	DR (Recessed)	C (Custom Col)				4 (4000K)	DA (DALI)
	1121						65 (6500K)	TDA (Tridonic DALI)
	1401						TW (2700-6500K)	
	1681							
	1961							
	2241							
	L							

Tyke