



N-SERIES PRISMATIC

Physical

Housing Aluminium

Profile Colour White, Black, Custom colours on request

Mounting Type

Recessed, Surface Mounted, Suspended

Electrical

Voltage

AC 220-240v 50/60Hz

Control

Non-dimmable, 0-10V, DALI, DALI DT8 (Tunable white)

Optical

Beam Angle



70° 115° (Up)

CCT 2700, 3000,

4000, 6500K

2700-6500K (Tunable White)

CRI 80, 90

UGR > 19

Efficiency Up to 98 lm/W

SDCM 3

Certification

Warranty 5 years

Category

AS/NZS 60598.2.1

LM-80, LM79 and TM21

reports on request


Lifetime L90 >54000 h




Lower outputs available upon request. Standard profile lengths are listed, consult Novii for custom lengths and connector angles. All lengths are stated with internal drivers, smaller lengths are possible with drivers housed in adjoining N-Series lengths. Tunable White versions of 841mm, 561mm and 281mm lengths need drivers housed in adjoining N-Series lengths. Tunable White L/T/X are larger due to driver length, consult Novii for lengths. Indirect DALI models are available in single or dual DALI control. All L/T/X connectors have internal drivers.

Direct

Surface Mounted, Suspended



Recessed



Length (mm)	W	Lm @4000K/@80CRI
281	7W	579
561	14W	1159
841	20W	1655
1121	27W	2235
1401	35W	2896
1681	41W	3393
1961	47W	3889
2241	54W	4469
L (548x548)	26W	2151
T (600x300)	21W	1738
X (600x600)	29W	2400




LM-80

Accessories

SKU	Accessories
T2-NECOP	Surface mounted/Suspended profile end cap (single)
T2-NECROP	Recessed profile end cap (single)
T2-SUS	Suspension kit (4m cable, pair)
T2-NSCD	Straight connector direct (Single)
T2-NSCI	Straight connector indirect (Single)

Indirect

Suspended



Length (mm)	W	Lm @4000K/@80CRI
281	4W	539
561	8W	1077
841	13W	1750
1121	16W	2154
1401	19W	2558
1681	24W	3231
1961	28W	3770
2241	32W	4308
L (548x548)	16W	2154
T (600x300)	14W	1885
X (600x600)	17W	2289

For combined Direct/Indirect data download IES file from website

SKU	Accessories
T2-NWC	Wall clip (Pair)
T2-NCR	Ceiling rose (Single)
T2-NRS	Rod suspension (1m, pair)
T2-NSM	Surface mounted kit (Pair)
T2-NBP	Blanking plate (1m)

SKU Builder

Series	Length	Optic	Profile Type	Profile Colour	CRI	CCT	Control
T2-N	281	P (Prismatic)	D (Direct)	B (Black)	8 (80)	27 (2700K)	N (Non-dim)
	561		I (Direct/Indirect)	W (White)	9 (90)	3 (3000K)	D10 (0-10V)
	841		DR (Recessed)	C (Custom Col)		4 (4000K)	DA (DALI)
	1121					65 (6500K)	TDA (Tridonic DALI)
	1401					TW (2700-6500K)	
	1681						
	1961						
	2241						
	L						
	T						
	X						

Tyke