



# IP65 Batten

Model : F3-60BIP

## Physical

**Trim finish** Light Grey

### Mounting type

Surface mounted,  
Suspended

## Electrical

### Voltage

AC 220-240, 50/60 Hz

**Control** Non-dimmable,  
DALI

Emergency CO/C90 D25,  
Battery Hrs 3

## Optical

**Beam angle** 160°

**CCT** 2700, 3000,  
4000, 5000K

**CRI** 80/90

**Efficiency** 130lm/W

## Certification

**Warranty** Fitting 5 years  
Battery 3 years

**Category** IP65, IK10

AS/NZS 60598.2.1  
AS/NZS 60598.2.22  
AS/NZS 2293.3

## Features



Integrated  
emergency option



IP65



IK10

## Product Specification

SKU	Wattage	Lumen Output (4000k)	EM Output (80CRI / 2700K)	Dimensions LxWxH mm	Technical Drawing
F3-20BIP	20W	2687lm	314lm	600 x 125 x 88	
F3-40BIP	40W	5373lm	315lm	1200 x 125 x 88	
F3-60BIP	60W	7628lm	317lm	1500 x 125 x 88	




## SKU

FB-SUS4

## Accessories

Suspension Kit

## Emergency Options

SKU	Non-dim	Dali
F3-20BIP		<input type="checkbox"/>
F3-40BIP		<input type="checkbox"/>
F3-60BIP		<input type="checkbox"/>

Replacement Battery YHBL-2-1.5B

Note: only models mentioned in table above come with emergency option

## SKU builder

Brand	Wattage	Size	Colour	CRI	CCT	Beam angle	Control
F3-	<ul style="list-style-type: none"> <li>XX</li> <li>-20 = 20W</li> <li>-40 = 40W</li> <li>-60 = 60W</li> </ul>	BIP-	G	<ul style="list-style-type: none"> <li>X</li> <li>-8 = 80CRI</li> <li>-9 = 90CRI</li> </ul>	<ul style="list-style-type: none"> <li>XX</li> <li>-27 = 2700K</li> <li>-3 = 3000K</li> <li>-4 = 4000K</li> <li>-5 = 5700K</li> </ul>	160	<ul style="list-style-type: none"> <li>XX</li> <li>-N = Non-Dim</li> <li>-DA = Dali</li> <li>-E = Emergency</li> </ul>

Example: F3-20BIP-G84160DA