



IP65 Batten

Model : F3-60BIP

Physical

Trim finish Light Grey

Mounting type

Surface mounted,
Suspended

Electrical

Voltage

AC 220-240, 50/60 Hz

Control Non-dimmable,
DALI

Emergency CO/C90 D25,
Battery Hrs 3

Optical

Beam angle 160°

CCT 2700, 3000,
4000, 5000K

CRI 80/90

Efficiency 130lm/W

Certification

Warranty Fitting 5 years
Battery 3 years

Category IP65, IK10

AS/NZS 60598.2.1
AS/NZS 60598.2.22
AS/NZS 2293.3

Features



Integrated
emergency option



IP65



IK10

Product Specification

SKU	Wattage	Lumen Output (4000k)	EM Output (80CRI / 2700K)	Dimensions LxWxH mm	Technical Drawing
F3-20BIP	20W	2687lm	314lm	600 x 125 x 88	
F3-40BIP	40W	5373lm	315lm	1200 x 125 x 88	
F3-60BIP	60W	7628lm	317lm	1500 x 125 x 88	




SKU

FB-SUS4

Accessories

Suspension Kit

Emergency Options

SKU	Non-dim	Dali
F3-20BIP		<input type="checkbox"/>
F3-40BIP		<input type="checkbox"/>
F3-60BIP		<input type="checkbox"/>

Replacement Battery YHBL-2-1.5B

Note: only models mentioned in table above come with emergency option

SKU builder

Brand	Wattage	Size	Colour	CRI	CCT	Beam angle	Control
F3-	<ul style="list-style-type: none"> XX -20 = 20W -40 = 40W -60 = 60W 	BIP-	G	<ul style="list-style-type: none"> X -8 = 80CRI -9 = 90CRI 	<ul style="list-style-type: none"> XX -27 = 2700K -3 = 3000K -4 = 4000K -5 = 5700K 	160	<ul style="list-style-type: none"> XX -N = Non-Dim -DA = Dali -E = Emergency

Example: F3-20BIP-G84160DA