


TRAIL

610-1253031314050

TRAIL LIGHT INSERT MOUNTING RAIL LIGHT INSERT made of aluminium, white, similar to RAL 9016, linear optics beam 90°, light output direct, with converter, max. 600mA, dimmability: not dimmable, through wiring IP40




DRAWING



TECHNICAL DETAILS

System perform. [W]	122
Bulb type	LED
Luminous flux [lm]	19050
Current sec. [mA]	600
Colour temp. [K]	4000K
CRI	>80
Optics	high quality linear optics
Designer	INHOUSE
Converter	with converter
Dimming	not dimmable
Light output	direct
Beam angle [°]	90°
Voltage [V]	220-240V 50/60Hz
Through wiring	7-polig
Material	aluminium
Length [mm]	2255
Width [mm]	64
Height [mm]	16
IP protection class	IP40
Voltage class	protection cl. I
Shock resistance	IK06
Net weight [kg]	2,10
Color lamp	white
RAL	9016
EAN-Number	9010506608366
Lifetime [h]	L90 B10 50 000
Energy efficiency cl.	B
No. of luminaires B16A	12

LIGHT DISTRIBUTION CURVE



The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.