

# Commercial Fixed Downlight



Model: F3-35SD

## Physical

**Material** ADC12 Aluminium

**Trim finish** White, Black

**Mounting type** Recessed

## Electrical

**Voltage** AC 220-240, 50/60 Hz

**Plug** 0.6m

**Control** Non-dimmable, Triac, 1-10V, DALI

## Optical

**Beam angle** 90°

**CCT** 2700K, 3 CCT Switch (3000, 4000, 5700K)

**CRI** 80, 90

**UGR** >19

**Efficiency** 90-100lm/W

**SDCM** 3

## Certification

**Warranty** 5 years

**Category** IP44

**Lifetime L70** 50000 Hrs AS/NZS 60598.2.2A

## Features



3 CCT Switch



IP 44



High Efficiency

## Product Specification

SKU	Wattage	Lumen Output (80CRI / 4000K)	Dimensions DxH mm	Cutout D mm	Technical Drawing
F3-10SD*	10W	827lm	85 x 39.5	70-75	
F3-13SD*	13W	1197lm	110 x 38	90-100	
F3-18SD	18W	1771lm	145 x 45	120-130	
F3-25SD	25W	2230lm	170 x 45	140-150	
F3-35SD	35W	3500lm	228 x 45	200-210	
F3-25SDL	25W	2428lm	280 x 52	230-260	