

# Commercial Fixed Downlight



Model: F3-35SD

## Physical

**Material** ADC12 Aluminium

**Trim finish** White, Black

**Mounting type** Recessed

## Electrical

**Voltage**  
AC 220-240, 50/60 Hz

**Plug** 0.6m

**Control** Non-dimmable,  
Triac, 1-10V, DALI

## Optical

**Beam angle** 90°

**CCT** 2700K, 3 CCT Switch  
(3000, 4000, 5700K)

**CRI** 80, 90

**UGR** >19

**Efficiency** 90-100lm/W

**SDCM** 3

## Certification

**Warranty** 5 years

**Category** IP44

**Lifetime L70** 50000 Hrs  
AS/NZS 60598.2.2A

## Features



3 CCT Switch



IP 44



High Efficiency

## Product Specification

| SKU      | Wattage | Lumen Output<br>(80CRI / 4000K) | Dimensions<br>DxH mm | Cutout<br>D mm | Technical<br>Drawing |
|----------|---------|---------------------------------|----------------------|----------------|----------------------|
| F3-10SD* | 10W     | 827lm                           | 85 x 39.5            | 70-75          |                      |
| F3-13SD* | 13W     | 1197lm                          | 110 x 38             | 90-100         |                      |
| F3-18SD  | 18W     | 1771lm                          | 145 x 45             | 120-130        |                      |
| F3-25SD  | 25W     | 2230lm                          | 170 x 45             | 140-150        |                      |
| F3-35SD  | 35W     | 3500lm                          | 228 x 45             | 200-210        |                      |
| F3-25SDL | 25W     | 2428lm                          | 280 x 52             | 230-260        |                      |