

# Surface Wall Pack



Model: F3-SW40/70

Model: F3-SW30

## Physical

**Material** Aluminium, Corrosion Resistant Powder coat  
**Optics** Polycarbonate Lens  
**Finish** Black RAL9017, Grey RAL9006  
**Mounting type** Surface mounted

## Electrical

**Voltage** AC 220-240, 50/60 Hz  
**Control** Non-dimmable, DALI

## Optical

**Beam angle** Asymmetric  
**CCT** 3000K, 4000K, 5000K  
**CRI** 70, 80  
**Efficiency** 136lm/W  
**SDCM** 3

## Certification

**Warranty** 5 Years Standard  
8 Years Extended  
**Category** IP66, IK08  
**Lifetime** L80 >82,000 Hrs  
**Salt Spray** 3000 Hrs testing  
 AS/NZS 60598.2.5  
 AS/NZS 60598.1




IP66



IK08



Salt Spray testing



Extended Lifespans



Integrated Photocell option

## Product Specification

SKU	Wattage	Lumen Output (80CRI / 4000K)	Efficiency	Dimensions HxWxL mm	Technical Drawing
F3-EW30	30W	4081lm	136lm/W	196 x 96 x 186	
F3-EW40	40W	5442lm	136lm/W	282 x 125 x 205	
F3-EW70	70W	9524lm	136lm/W	282 x 125 x 205	


## SKU builder

Brand	Wattage	Colour	CRI	CCT	Beam angle	Control	Accessories
F3-SW FluxLED Surface Wall	XX - -30 = 30W -40 = 40W -70 = 70W	X -B = Black -G = Grey	X -7 = 70CRI -8 = 80CRI -9 = 90CRI	X -3 = 3000K -4 = 4000K -5 = 5000K	FAS -FAS = Flood Asymmetric	X - -N = Non-dim -DA = DALI 2	X -P = Photocell


Example: F3-SW40-G84ASN-P

## Beam angle options

Lumen outputs @ 4000K, 80CRI





**FAS= Asymmetric**  
30W = 4081 Lm







**FAS= Asymmetric**  
40W = 5442 Lm  
70W = 9524 Lm

## Product Dimensions



F3-EW30



F3-EW40  
F3-EW70

