



\*Tamper-proof option

GLARE CONTROL  
CIRCADIAN RHYTHM  
LIGHTING CONTROL  
FLICKER MANAGEMENT



## Compose IP65 Diffuse

SKU	W	Lm @4000K/@80CRI	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-CIP1D10*	10	762	Fixed	Ø 83	
G2-CIP2D13*	13	1003	Fixed	Ø 92	
G2-CIP3D18	18	1762	Fixed	Ø 127	
G2-CIP3D25	25	2429	Fixed	Ø 127	
G2-CIP4D18	18	1872	Fixed	Ø 152	
G2-CIP4D25	25	2610	Fixed	Ø 152	
G2-CIP4D30	30	3201	Fixed	Ø 152	
G2-CIP5D18	18	1848	Fixed	Ø 202	
G2-CIP5D25	25	2608	Fixed	Ø 202	
G2-CIP5D35	35	3503	Fixed	Ø 202	

\*Beam angles available for specific product(s)



### Physical

**Housing** Glass/Aluminium

**Reflector Finish** Faceted Silver

**Trim Finish** White, Black

**Mounting Type** Recessed

### Electrical

**Voltage**


AC 220-240v 50/60Hz

**Control**

Non-dimmable, Triac,  
1-10V, DALI, TW (DALI DT8)

### Optical

**Beam Angle**



\*75° 90°

**CCT** 2700, 3000, 4000, 5700K

CCT Select (3000K-5700K)

Tunable White (3000K-5700K)

**CRI** 80, 90

**UGR** >19

**Efficiency** 77-109lm/W

### Certification

**Warranty** 5 years

**Category**

AS/NZS 60598.2.2A

TM21 report on request



IP65 IK06/08