



*Tamper-proof option

GLARE CONTROL
LIGHTING CONTROL
FLICKER MANAGEMENT



Compose IP65 Lens

SKU	W	Lm @4000K/@80CRI	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-CIP1L10*	10	937	Fixed	Ø 83	
G2-CIP2L13*	13	1048	Fixed	Ø 92	
G2-CIP3L18	18	2013	Fixed	Ø 127	
G2-CIP3L25	25	2600	Fixed	Ø 127	
G2-CIP4L18	18	1726	Fixed	Ø 152	
G2-CIP4L25	25	2512	Fixed	Ø 152	
G2-CIP4L30	30	3190	Fixed	Ø 152	
G2-CIP5L18	18	1754	Fixed	Ø 202	
G2-CIP5L25	25	2442	Fixed	Ø 202	
G2-CIP5L35	35	3177	Fixed	Ø 202	

*Beam angles available for specific product(s)



Physical

Housing Glass/Aluminium

Reflector Finish Faceted Silver

Trim Finish White, Black

Mounting Type Recessed

Electrical

Voltage


AC 220-240v 50/60Hz

Control

Non-dimmable, Triac,
1-10V, DALI

Optical

Beam Angle



CCT 2700, 3000, 4000, 5700K

CRI 80, 90

UGR >19

Efficiency 85-112lm/W

Certification

Warranty 5 years

Category

AS/NZS 60598.2.2A

TM21 report on request



grace