

H-SERIES

Physical

Housing Aluminium
Profile Colour White, Black, Custom colours on request
Mounting Type Surface Mounted, Suspended

Electrical

Voltage AC 220-240v 50/60Hz
Control Non-dimmable, 0-10V, DALI, DALI DT8 (Tunable white)

Optical

Beam Angle



90°

CCT 2700, 3000, 4000, 6500K
 2700-6500K (Tunable White)
CRI 80, 90
UGR > 19
Efficiency 111lm/W
SDCM 3

Certification

Warranty 5 years

Category

AS/NZS 60598.2.1
 LM-80, LM79 and TM21 reports on request

Lifetime L90 >54000h




IP20

Lower outputs available upon request.
 5% Tolerance on stated lumen output and wattage.

Direct

Surface Mounted,
 Suspended



Diameter (mm)	W	Lm @4000K/@80CRI
1600	105W	11744
1800	125W	13981
2000	156W	17448



Accessories

SKU	Accessories
T2-HNCR	Ceiling rose (Single)
T2-HNRS	Rod suspension (1m, Kit)
T2-HNSM	Surface mounted kit (Kit)

SKU Builder

Series	Diameter	Optic	Profile Type	Profile Colour	CRI	CCT	Control
T2-H	1600	O (Opal)	D (Direct)	B (Black)	8 (80)	27 (2700K)	N (Non-dim)
	1800			W (White)	9 (90)	3 (3000K)	DA (DALI)
	2000			C (Custom Col)		4 (4000K)	TDA (Tridonic DALI)
						65 (6500K)	
						TW (2700-6500K)	