

fluxxLED

pull-out downlight

pull-out downlight

fluxxLED



Model shown: F3-FCA15

Product Specification

SKU	Wattage	Lumen Output (80CRI / 4000K)	Dimension DxH/LxWxH mm	Cutout D mm (LxW mm)
F3-FCA15	15W	1290lm	100 x 114 (56D)	83-89
F3-FCA30	30W	2580lm	180 x 100 x 114 (56)	85 x 165
F3-FCA42	42W	3600lm	260 x 100 x 114 (56)	85 x 245



*F3-FCA15 complies with IC when manufactured at 13W use code F3-FCA13
*F3-FCA30 complies with IC when manufactured at 26W use code F3-FCA26

Product Dimensions

SKU	
F3-FCA15	
F3-FCA30	
F3-FCA42	

Physical

Material
ADC12 Aluminium

Finish
White / Black

Mounting Type
Recessed

Rotation / Tilt Angle
80° / 360°

Electrical

Voltage
AC 220-240, 50/60 Hz

Control
Triac / DALI

Optical

Beam Angle
24° / 36°

CCT
2700K, 3000K, 4000K, 5000K

CRI
80 / 90

UGR
> 19

Efficiency
86lm/W

Certification

Warranty
5 years

Category
IP20

Lifetime
L70B10 >50000 Hrs

AS/NZS 60598.2.2A

CE RoHS

IP20