



## CLEAN ROOM HB /840 HE



OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	∠	Total power [W]
9040111XY	LED	500/500/60	485/485/100	7.00	10840	82°	74.0

**GENERAL** Recessed luminaire for direct illumination, constructed especially for production plants according to HACCP standards (food and beverage industry), with ambience temperature range -20°C + 45°C. Luminaire efficiency is ensured with highly efficient optical and electronic components.

**OPTICS** Tempered glass diffuser with special anti-scattering film in case of breakage.

**LIGHTING MANAGEMENT** The choice of appropriate control gear enables integration into different building management systems (BMS).


**HOUSING** Housing is made of steel sheet, 0,8 mm thick, epoxy-polyester powder coated. Fine structured texture. Double anodized aluminium profile holds the optics providing a high mechanical protection degree (IP65).

**FEATURES** The luminaire is serviceable from above, with access to LED modules and drivers from the suspended ceiling zone, without removing or dismantling the luminaire.

**APPLICATION** Applicable in spaces requiring maintenance from above (ceiling area), without compromising the cleanliness or operation of the space below.

**EQUIPMENT** Supplied with mounting kit.

**ADDITIONAL** Zinc primer housing coating for corrosion prevention available upon request.



CCT	
4000 K	
CRI	UGR
>80	<22
LED Service life	
60000h L80 B10 /SDCM 3	



\* Luminaire luminous flux and connected electrical load - initial tolerance of ±10 % (at ambient temperature of 25°C).  
 \*\* Add '-4' on ordering code for 1-10V control gear  
 \*\* Add '-5' on ordering code for DALI control gear or  
 \*\* Replace XY with the color code when ordering ( e.g. 11 white, 21 grey, 31 black).