



\*Tamper-proof option

GLARE CONTROL  
LIGHTING CONTROL  
FLICKER MANAGEMENT



## Compose IP65 Lens

SKU	W	Lm @4000K/@80CRI	Tilt (T) Rotation (R) °	Cutout (mm)	Dimensions (mm)
G2-CIP1L6*	6	558	Fixed	Ø 83	
G2-CIP2L13*	13	1048	Fixed	Ø 92	
G2-CIP3L18	18	2013	Fixed	Ø 127	
G2-CIP3L25	25	2600	Fixed	Ø 127	
G2-CIP4L18	18	1726	Fixed	Ø 152	
G2-CIP4L25	25	2512	Fixed	Ø 152	
G2-CIP4L30	30	3190	Fixed	Ø 152	
G2-CIP5L18	18	1754	Fixed	Ø 202	
G2-CIP5L25	25	2442	Fixed	Ø 202	
G2-CIP5L35	35	3177	Fixed	Ø 202	

\*Beam angles available for specific product(s)



### Physical


**Housing** Glass/Aluminium  
**Reflector Finish** Faceted Silver  
**Trim Finish** White, Black  
**Mounting Type** Recessed

### Electrical

**Voltage**  
AC 220-240v 50/60Hz  
**Control**  
Non-dimmable, Triac,  
1-10V, DALI

### Optical

#### Beam Angle



**CCT** 2700, 3000, 4000, 5700K  
**CRI** 80, 90  
**UGR** >19  
**Efficiency** 85-112lm/W

### Certification

**Warranty** 5 years  
**Category**  
AS/NZS 60598.2.2A  
TM21 report on request



grace