


TITAN 1500 /840 HO



CE	IP66	LED
		220V 240V
CLASS 1		50Hz 60Hz

OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	Total power [W]
6511151XY	LED	1573/104/84	-	2.00	6960	45.0

GENERAL Surface mounted watertight (IP66) high efficiency LED luminaire.

OPTICS Polycarbonate opal diffuser, UV stabilized.


HOUSING Self-extinguishing polycarbonate.

FEATURES Maximal ambient temperature $t_a=40^{\circ}\text{C}$.

APPLICATION Direct mounting to the ceiling, wall or using suspension kit.

EQUIPMENT Supplied with surface mounting kit.

ADDITIONAL Suspension kit, IP connector. Additional options: through wiring, DALI, EM.



CCT	
4000 K	
CRI	UGR
>80	<25
LED Service life	
60000h L80B10 /SDCM3	



* Luminaire luminous flux and connected electrical load - initial tolerance of $\pm 10\%$ (at ambient temperature of 25°C).

** Add '-4' on ordering code for 1-10V control gear

** Add '-5' on ordering code for DALI control gear or

** Replace XY with the color code when ordering (e.g. 11 white, 21 grey, 31 black).