


## TITAN 1500 /840 HE



CE	IP66	LED
		220V 240V
CLASS 1		50Hz 60Hz

OC ECG **	Socket	A/B/H[mm]	a/b/h[mm]	Weight [kg]	Flux [lm]*	Total power [W]
6511152XY	LED	1573/104/84	-	2.00	4602	28.0

**GENERAL** Surface mounted watertight (IP66) high efficiency LED luminaire.

**OPTICS** Polycarbonate opal diffuser, UV stabilized.


**HOUSING** Self-extinguishing polycarbonate.

**FEATURES** Maximal ambient temperature  $t_a=40^{\circ}\text{C}$ .

**APPLICATION** Direct mounting to the ceiling, wall or using suspension kit.

**EQUIPMENT** Supplied with surface mounting kit.

**ADDITIONAL** Suspension kit, IP connector. Additional options: through wiring, DALI, EM.



CCT	
4000 K	
CRI	UGR
>80	<25
LED Service life	
60000h L80B10 /SDCM3	



\* Luminaire luminous flux and connected electrical load - initial tolerance of  $\pm 10\%$  (at ambient temperature of  $25^{\circ}\text{C}$ ).

\*\* Add '-4' on ordering code for 1-10V control gear

\*\* Add '-5' on ordering code for DALI control gear or

\*\* Replace XY with the color code when ordering ( e.g. 11 white, 21 grey, 31 black).