

# BOBY WALWASHER



## General data:

Luminaire body: aluminum  
Mounting type: track 230V  
Ingress protection IP: IP20  
operating temperature range: from -40°C to +40°C  
Lifetime L80B10: 100 000h

## Electrical data:


Nominal voltage: 220-240V AC  
Nominal frequency: 50-60 Hz  
Protection class: I  
Contains light source: yes  
Tolerance of luminous flux: on-off, DALI (on request: CASAMBI)

## Optical data:

Optical system: reflector  
Material: PC  
Light distribution: wallwasher

## Lighting data:

Light source: LED  
Colour rendering index: CRI>90 (on request: CRI>95)  
Tolerance of luminous flux: +/-10%



## E-electronics

O- on-off

D- Dali



## C- colour

Catalogue code	Luminaire light flux	Power	Effectiveness	Color temperature	CRI/RA	Weight	Dimensions	Box dimensions
2014.02EC	1269lm	14 W	91lm /W	27 00K	≥90	0,8kg	Ø120 H=150mm	300x220x200mm
2014.03EC	1322lm	14 W	94 lm /W	3000K	≥90	0,8kg	Ø120 H=150mm	300x220x200mm
2014.04 EC	1377lm	14 W	98lm /W	4 000K	≥90	0,8kg	Ø120 H=150mm	300x220x200mm
2015.02EC	1829lm	20W	91lm /W	27 00K	≥90	0,8kg	Ø120 H=150mm	300x220x200mm
2015.03EC	1905lm	20W	95lm /W	3000K	≥90	0,8kg	Ø120 H=150mm	300x220x200mm
2015.04 EC	1984 lm	20W	99lm /W	4 000K	≥90	0,8kg	Ø120 H=150mm	300x220x200mm