


DISCOVERY POWER LED




General data:

Mounting:	on an adjustable holder, to the ground
Casing:	aluminium
Ingress protection IP:	66
Operating temperature range:	from -40° to +45°
Żywotność L80B10:	100 000h



Dane elektryczne:

Nominal voltage:	220-240V AC
Nominal frequency:	50-60Hz
luminaire nominal power:	5W-50W
Protection class:	I
Connection:	wire 3x0,75mm ² (5x0,75mm ² for DALI)
Wiring:	through, standard
Connection wire:	0,5m
Dimming:	ON-OFF, DALI
Power supply:	inside the luminaire



Optical data:

Optical system:	lens
Material:	PMMA
Light emission:	direct
Light distribution:	symetryczny, asymetryczny


Dane świetlne:

Light source:	LED
Colour rendering index:	CRI>80
Colour tolerance SDCM:	SDCM<3
Tolerance of luminous flux:	+/-10%

Discovery is a linear luminaire with a slim construction based on an aluminum profile, using high-quality LED modules. Thanks to a wide range of optics, the luminaire is able to meet the assumptions of the most demanding projects. The use of an appropriate lighting control system allows you to obtain unique light scenes. The Discovery luminaire is designed to illuminate the facades of modern, classic, historical buildings, urban buildings, housing estates, hotels, restaurants.

L - lenses available:

10 - 10°
20 - 20°
40 - 40°
60 - 60°
41 - 45°x10
8 - 8° wall-wash
45 - 45° wall-wash
02 - asymmetrical



W - wiring

T- through
S- standard

E - electronic

O- On-Off
D- DALI

C -colour

Catalogue code	Luminaire light flux	Power	Effectiveness	Color temperature	CRI/RA	Weight	Box dimensions
9160.02ELCW	1070lm	9W	119lm/W	2700K	≥80	1,4 kg	450x200x150mm
9160.03ELCW	1115lm	9W	119lm/W	3000K	≥80	1,4 kg	450x200x150mm
9160.04ELCW	1162lm	9W	119lm/W	4000K	≥80	1,4 kg	450x200x150mm
9161.02ELCW	1606lm	13W	124lm/W	2700K	≥80	1,4 kg	450x200x150mm
9161.03ELCW	1673lm	13W	124lm/W	3000K	≥80	1,4 kg	450x200x150mm
9161.04ELCW	1742lm	13W	124lm/W	4000K	≥80	1,4 kg	450x200x150mm

Accessories

connector IP 68 3-pole

catalogue number 124.00



Raster

On request

