


DISCOVERY RGBW




General data:

| | |
|------------------------------|--|
| Luminaire body: | aluminum |
| Mounting type: | on an adjustable holder, to the ground |
| Ingress protection IP: | 66 |
| Operating temperature range: | from -40° to +45° |
| Lifetime L80B10: | 100 000h |



Dane elektryczne:

| | |
|--------------------------|----------------------|
| Nominal voltage: | 220-240V AC |
| Nominal frequency: | 50-60Hz |
| luminaire nominal power: | 9W |
| Protection class: | I |
| Connection: | 8x0,3mm ² |
| Wiring: | through, standard |
| Connection wire: | 0,5m |



Optical data:

| | |
|---------------------|---------------------------|
| Optical system: | lens |
| Material: | PMMA |
| Light emission: | direct |
| Light distribution: | symmetrical, asymmetrical |


Dane świetlne:

| | |
|-----------------------------|--------|
| Light source: | LED |
| Colour rendering index: | CRI>80 |
| Colour tolerance SDCM: | SDCM<3 |
| Tolerance of luminous flux: | +/-10% |

Discovery is a linear luminaire with a slim construction based on an aluminum profile, using high-quality LED modules. Thanks to a wide range of optics, the luminaire is able to meet the assumptions of the most demanding projects. The use of an appropriate lighting control system allows you to obtain unique light scenes. The Discovery luminaire is designed to illuminate the facades of modern, classic, historical buildings, urban buildings, housing estates, hotels, restaurants.

L - lenses available:

10 - 10°
20 - 20°
40 - 40°
60 - 60°
41 - 45°x10
8 - 8° wall-wash
45 - 45° wall-wash
02 - asymmetrical



W - wiring

T- through
S- standard

C -colour

| Catalogue code | Luminaire light flux | Power | Color temperature | CRI/RA | Weight | Box dimensions |
|----------------|----------------------|-------|-------------------|--------|--------|----------------|
| 9273.52LCW | 611lm | 9W | 2700K | ≥80 | 1,4 kg | 450x200x150mm |
| 9273.53LCW | 621lm | 9W | 3000K | ≥80 | 1,4 kg | 450x200x150mm |
| 9273.54LCW | 632lm | 9W | 4000K | ≥80 | 1,4 kg | 450x200x150mm |

Accessories

embranchment IP67

catalogue code 90.10



connector IP68 3pole

catalogue code 124.00

