

FIX 75



General data:

Luminaire body: aluminum
Mounting: track 230V
Ingress protection IP: IP20
Operating temperature: from -40°C to +40°C
Lifetime L80B10: 100 000h

Electric data:


Nominal voltage: 220-240V AC
Nominal frequency: 50-60 Hz
Protection class: I
Dimming: on-off, DALI (on request: CASAMBI)

Optical data:

Optical system: lens
Material: PMMA
Light distribution: symmetrical
Lenses available: 36°

Lighting data:

Light source: LED
Colour rendering index: CRI>90 (on request: CRI>95)
Tolerance of luminous flux: +/-10%



Fix is a range of projectors with a simple shape, yet characterized by excellent performance: excellent colour rendering and colour temperature options to choose from. Available in three sizes. Suitable for use in commercial spaces, showrooms, museums, art galleries and private apartments.

E- elektronika

O- on-off

D- Dali

C- colour

L – soczewki

36°



Catalogue code	Light flux	Power	Effectiveness	Color temperature	CRI/RA	Weight	Dimensions	Box dimensions
2006.02ELC	1369lm	12W	114lm/W	2700K	>90	0,8kg	Ø75 H=105mm	300x200x120mm
2006.03ELC	1427lm	12W	119lm/W	3000K	≥90	0,8kg	Ø75 H=105mm	300x200x120mm
2006.04ELC	1486lm	12W	124lm/W	4000K	≥90	0,8kg	Ø75 H=105mm	300x200x120mm

Accessories

Antiglare honey comb

catalogue code 20.06

