

FIX- 90



TECHNICAL DATA:

Luminaire body: aluminium
Mounting: track 230V
Ingress protection IP: IP20
Operating temperature range: from -40°C to +40°C
Lifetime L80B10: 100 000h

Electric data:

Nominal voltage: 220-240V AC
Lighting Nominal voltage: 50-60 Hz
Protection class: I
Contains light source: Yes
Dimming: on-off, DALI (CASAMBI - on request)


Optical data:

Nominal voltage: lens
Material: PMMA
Light distribution: symmetric
Lenses available: 36°

Lighting data:

Light source: LED
Colour rendering index: CRI>90 (CRI>95 - on request)
Tolerance of luminous flux: +/-10%


Fix is a range of projectors with a simple shape, yet characterized by excellent performance: excellent colour rendering and colour temperature options to choose from. Available in three sizes. Suitable for use in commercial spaces, showrooms, museums, art galleries and private apartments.



E- elektronika

O- on-off

D- Dali



C- colour

L – soczewki

36°

Catalogue code	Light flux	Power	Effectiveness	Color temperature	CRI/RA	Weight	Dimensions	Box dimensions
2008.02ELC	2075lm	19W	109lm/W	2700K	≥90	0,9kg	Ø90 H=120mm	300x200x120mm
2008.03ELC	2162lm	19W	114lm/W	3000K	≥90	0,9kg	Ø90 H=120mm	300x200x120mm
2008.04 ELC	2252lm	19W	119lm/W	4000K	≥90	0,9kg	Ø90 H=120mm	300x200x120mm

Accessories

Antiglare honey comb

catalogue code 20.08

