

## FIX- 90



### TECHNICAL DATA:

Luminaire body:	aluminium
Mounting:	surface mounted
Ingress protection IP:	IP20
Operating temperature range:	from -40°C to +40°C
Lifetime L80B10:	100 000h

### Electric data:

Nominal voltage:	220-240V AC
Lighting Nominal voltage:	50-60 Hz
Protection class:	I
Contains light source:	Yes
Dimming:	on-off, DALI (CASSAMBI - on request)


### Optical data:

Nominal voltage:	lens
Material:	PMMA
Light distribution:	symmetric
Lenses available:	36°

### Lighting data:

Light source:	LED
Colour rendering index:	CRI>90 (CRI>95 - on request)
Tolerance of luminous flux:	+/-10%

Fix is a range of projectors with a simple shape, yet characterized by excellent performance: excellent colour rendering and colour temperature options to choose from. Available in three sizes. Suitable for use in commercial spaces, showrooms, museums, art galleries and private apartments.



**E- elektronika**

O- on-off

D- Dali



**C- colour**

**L – soczewki**

36°

Catalogue code	Light flux	Power	Effectiveness	Color temperature	CRI/RA	Weight	Dimensions	Box dimensions
2086.02ELC	2075lm	19W	109lm/W	2700K	≥90	0,9kg	Ø90 H=160mm	300x200x120mm
2086.03ELC	2162lm	19W	114lm/W	3000K	≥90	0,9kg	Ø90 H=160mm	300x200x120mm
2086.04 ELC	2252lm	19W	119lm/W	4000K	≥90	0,9kg	Ø90 H=160mm	300x200x120mm

## Accessories

Antiglare honey comb

catalogue code 20.08

