

FLAP WALLWASHER



General data:

Luminaire body:	aluminum
Mounting type:	surface mounted
Ingress protection IP:	IP20
operating temperature range:	from -40°C to +40°C
Lifetime L80B10:	100 000h

Electrical data:


Nominal voltage:	220-240V AC
Nominal frequency:	50-60 Hz
Protection class:	I
Contains light source:	yes
Dimming:	on-off, DALI (on request: CASAMBI)

Optical data:

Optical system:	reflector
Material:	PC
Light distribution:	wallwasher

Lighting data:

Light source:	LED
Colour rendering index:	CRI>90 (on request CRI>95)
tolerance of luminous flux:	+/-10%



E-electronics

O- on-off

D- Dali



C- colour

Catalogue code	Luminaire light flux	Power	Effectiveness	Color temperature	CRI/RA	Weight	Dimensions	Box dimensions
2013.02EC	1268lm	9W	70lm/W	2700K	≥90	0,7 kg	Ø120 H=190mm	300x220x200mm
2081.03EC	659lm	9W	73lm/W	3000K	≥90	0,7 kg	Ø120 H=190mm	300x220x200mm
2081.04EC	687lm	9W	76lm/W	4000K	≥90	0,7 kg	Ø120 H=190mm	300x220x200mm
2082.02EC	1268lm	15W	85lm/W	2700K	≥90	0,7 kg	Ø120 H=190mm	300x220x200mm
2082.03EC	1320lm	15W	88lm/W	3000K	≥90	0,7 kg	Ø120 H=190mm	300x220x200mm
2082.04EC	1375lm	15W	92lm/W	4000K	≥90	0,7 kg	Ø120 H=190mm	300x220x200mm